



ProLED. MR11 & MR16

Halco
LIGHTING TECHNOLOGIES

Energy Efficient

- Up to 80% energy savings compared to standard halogen lamps

Technical Data

- MR11 and MR16
- 2, 3, 5 and 6 watts
- 12 Volt DC
- 40,000 hours average rated life
- Warm White, Natural White, Amber, Blue, Green and Red
- 25°, 40°, 60° and 120° beam spreads

Construction

- USA and Japanese manufactured chips
- European optics
- Proprietary driver provides optimal electrical characteristics for each lamp type
- Extruded aluminum heat-sink

Benefits

- Precise beam control
- No UV
- Does not project heat
- Reduced Maintenance
- Consistent lamp-to-lamp color
- Safe for open fixture operation

Mercury Free, No UV, No Projected Heat.

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at halcolighting.com.

Your account representative is your single source for pricing, orders, and technical support.

Shipping from Atlanta, Cleveland, Houston, and Phoenix.



**where there's light,
there's halco®**

(800) 677-3334

halcolighting.com

Bulb Type	Watts	Base	Item#	Product Code	Description	Volts	Color Temp.	Lumens	CBCP	Useful Life*	Pkg. Qty.	Beam Spread	MOL	
MR11 & MR16 Lamps														
MR11	2	G4	80603	MR11/2NW25/LED	Natural White	12	5600	80	470	40000	1/10	25°	1.39"	
MR11	2	G4	80600	MR11/2WW25/LED	Warm White	12	3100	68	380	40000	1/10	25°	1.39"	
MR11	2	G4	80604	MR11/2NW40/LED	Natural White	12	5600	80	140	40000	1/10	40°	1.39"	
MR11	2	G4	80601	MR11/2WW40/LED	Warm White	12	3100	68	110	40000	1/10	40°	1.39"	
MR11	2	G4	80605	MR11/2NW120/LED	Natural White	12	5600	80	40	40000	1/10	120°	1.39"	
MR11	2	G4	80602	MR11/2WW120/LED	Warm White	12	3100	68	30	40000	1/10	120°	1.39"	
MR16	3	G5.3	80608	MR16/3NW25/LED	Natural White	12	5600	140	-	40000	1/10	25°	2.1"	
MR16	3	G5.3	80606	MR16/3WW25/LED	Warm White	12	3100	110	-	40000	1/10	25°	2.1"	
MR16	3	G5.3	80609	MR16/3NW60/LED	Natural White	12	5600	140	-	40000	1/10	60°	2.1"	
MR16	3	G5.3	80607	MR16/3WW60/LED	Warm White	12	3100	110	-	40000	1/10	60°	2.1"	
MR16	5	G5.3	80619	MR16/5NW25/LED	Natural White	12	5600	180	2180	40000	1/10	25°	2"	
MR16	5	G5.3	80616	MR16/5WW25/LED	Warm White	12	3100	140	1750	40000	1/10	25°	2"	
MR16	5	G5.3	80614	MR16/M5NW40/LED	Natural White, 3 LEDs	12	5600	220	650	40000	1/10	40°	2"	
MR16	5	G5.3	80611	MR16/M5WW40/LED	Warm White, 3 LEDs	12	3100	190	520	40000	1/10	40°	2"	
MR16	5	G5.3	80620	MR16/5NW60/LED	Natural White	12	5600	180	440	40000	1/10	60°	2"	
MR16	5	G5.3	80617	MR16/5WW60/LED	Warm White	12	3100	140	350	40000	1/10	60°	2"	
MR16	5	G5.3	80625	MR16/5AMB60/LED	Amber	12	-	-	-	40000	1/10	60°	2"	
MR16	5	G5.3	80623	MR16/5BLU60/LED	Blue	12	-	-	-	40000	1/10	60°	2"	
MR16	5	G5.3	80624	MR16/5GRN60/LED	Green	12	-	-	-	40000	1/10	60°	2"	
MR16	5	G5.3	80622	MR16/5RED60/LED	Red	12	-	-	-	40000	1/10	60°	2"	
MR16	5	G5.3	80621	MR16/5NW120/LED	Natural White	12	5600	180	80	40000	1/10	120°	2"	
MR16	5	G5.3	80615	MR16/M5NW120/LED	Natural White, 3 LEDs	12	5600	220	110	40000	1/10	120°	2"	
MR16	5	G5.3	80618	MR16/5WW120/LED	Warm White	12	3100	140	60	40000	1/10	120°	2"	
MR16	5	G5.3	80612	MR16/M5WW120/LED	Warm White, 3 LEDs	12	3100	190	90	40000	1/10	120°	2"	
⊛	MR16	6	G5.3	80657	MR16/5M6WW40/LED	Warm White	23	3100	310	-	40000	1/10	40°	2"
⊛	MR16	6	G5.3	80658	MR16/5M6NW40/LED	Natural White	23	5600	385	-	40000	1/10	40°	2"

⊛NEW ITEM!

* Useful Life is Defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point, but at decreased light levels.

Warranty - Commercial / Industrial: This product is warranted for 5 years from the date of purchase, based on 10 hours of use per day.

Note: This product may not be compatible with some dimming devices or AC electronic transformers. Lamps should be tested in the application for compatibility prior to full installations on circuits using such devices.